

PATCH CORD CAT6 UTP, 26AWG, WHITE PVC

Features

- Cabling for category 5e (Cat5e) and 6 (Cat6) applications
- High durability connectors: RJ45 male
- PVC 4-pair stranded UTP
- Rated for 250MHz/ 1Gbps communication
- Available in different colors and lengths

General

Cable Type
 Operating Frequency
 Characteristic Impedance
 Conductor
 Jacket Material
 Jacket Color
 Connector
 Wiring
 Durability

Category 6
 250 MHz
 100 Ohm
 Stranded Copper
 PVC
 White
 RJ45
 T568B
 750 times

Dimensions

Conductor Diameter
 Isolation Diameter
 Diameter Over Jacket

26AWG
 0.75 mm
 5.20 mm

Technical

Operating Temperature
 Dielectric Strength
 Current Rating
 Insulation Resistance
 Contact Resistance
 Rated Voltage
 Data Transmission Rate

-20°C to +60°C
 1000 Vac (RMS)
 1.5 A
 500 MOhm Min.
 20 mOhm Max.
 72 Vdc Max.
 1000 Mbps

Compliance

Applicable
 Standards

RoHS2.0
 ANSI/TIA-568.2-D
 ISO/IEC 11801 Class E
 EN 50173-1



Proprietary information of SIGHTES TECHNOLOGY that may not be reproduced, disclosed or used for any purpose except under the authorized written consent of SIGHTES TECHNOLOGY and may be recalled at any time. Copyright 2022 SIGHTES TECHNOLOGY. All Rights Reserved May 31 2023