# **FOTUX®** Balanced Twisted-Pair Assembly

### FX-RJ45P6



# CAT6 ONE-PIECE RJ45, 8P8C UN-SHIELDED PLUG

#### **Features**

- Tailored for Cat6 twisted pair cables.
- Supports 10GBASE-T for high-speed networks.
- Eight-pin configuration ensures precise alignment.
- Contacts resist corrosion, ensuring durable connections.
- Simplified termination with compatibility for common tools.



## **General**

Interface
ANSI/TIA Category
Cable Type Compatible
Conductor Type Compatible
Module Material
Contact Material
Durability

RJ45
Category 6
Round, Unshielded
Solid | Stranded
Polycarbonate (PC)
Gold Plated Phosphor Bronze
750 times

#### **Dimensions**

Compatible Conductor Gauge insulation-piercing Diameter Contact Plating Thickness

24AWG to 23AWG 1.05 mm 1.27 μm

#### **Technical**

Operating Temperature Storage Temperature Plug Retention Force Current Rating Insulation Resistance Contact Resistance Voltage Tested -40°C to +80°C -40°C to +80°C 20 lbs Min. 250V AC, 2A@25°C 500MOhms Min, 100V DC/min 20 mOhm Max. 1000V AC/1 minute no breakdown

## **Compliance**

Applicable Standards

RoHS2.0 ANSI/TIA-568.2-D TIA-968-A | TIA-1096-A IEC 60603-7-4



