

60 TYPE FAST FIELD CONNECTOR

Features

- Fast and easy on-site installation with stability
- Eliminated field polishing
- No adhesives or electrical power required
- Reduced connection defect rate by re-assembling
- Compatible with 3*2mm flat cable, 3.0, 2.0 or 0.9mm drop cable



General

Interface

Splice Type

Fiber Mode

SC/APC (Green)

SC/UPC (Blue)

Mechanical

Single-mode

Dimensions

Cable Compatible

Connector Size

3.0*2.0 mm Flat

3.0/2.0/0.9 mm Round

55*9*7.3 mm

Technical

Operating Temperature

Cable Retention Strength

Retention On Bare Fiber

Insertion Loss

Return Loss

On-line Tensile Strength

Mechanical Durability

Drop-off Test

Reusable

-40 °C to +85 °C

45N Min.

2 to 3N (Ferrule System)

0.5dB Max.

0.3dB Avg.

55dB (APC) Min.

50dB (UPC) Min.

20N ($\Delta IL \leq 0.3dB$)

500 times ($\Delta IL \leq 0.3dB$)

4M*3 times ($\Delta IL \leq 0.3dB$)

>10 times

Compliance

Applicable

Standards

Regional Availability

RoHS2.0

IEC61754-4

TIA-604-3(FOCIS-3)

Latin America | EMEA



Proprietary information of SIGHTES TECHNOLOGY that may not be reproduced, disclosed or used for any purpose except under the authorized written consent of SIGHTES TECHNOLOGY and may be recalled at any time. Copyright 2022 SIGHTES TECHNOLOGY. All Rights Reserved May 31 2023