

### 10 TYPE FAST FIELD CONNECTOR

#### Features

- Fast and easy on-site installation with stability
- Eliminated field polishing
- No adhesives or electrical power required
- Reduced connection defect rate by re-assembling
- Compatible with 3\*2mm flat cable



#### General

Interface

Splice Type  
Fiber Mode

SC/APC (Green)  
SC/UPC (Blue)  
Mechanical  
Single-mode

#### Dimensions

Cable Compatible  
Connector Size

3.0\*2.0 mm Flat  
53.5\*9\*7.3 mm

#### Technical

Operating Temperature  
Cable Retention Strength  
Retention On Bare Fiber  
Insertion Loss

Return Loss

On-line Tensile Strength  
Mechanical Durability  
Drop-off Test  
Reusable

-40 °C to +85 °C  
45N Min.  
2 to 3N (Ferrule System)  
0.5dB Max.  
0.3dB Avg.  
55dB (APC) Min.  
50dB (UPC) Min.  
20N ( $\Delta IL \leq 0.3dB$ )  
500 times ( $\Delta IL \leq 0.3dB$ )  
4M\*3 times ( $\Delta IL \leq 0.3dB$ )  
>10 times

#### Compliance

Applicable  
Standards

Regional Availability

RoHS2.0  
IEC 61754-4  
TIA-604-3(FOCIS-3)  
Latin America | EMEA



Proprietary information of SIGHTES TECHNOLOGY that may not be reproduced, disclosed or used for any purpose except under the authorized written consent of SIGHTES TECHNOLOGY and may be recalled at any time. Copyright 2022 SIGHTES TECHNOLOGY. All Rights Reserved May 5 2025