

### Pole-Mounted NAP Box, One Pre-installed 16-splice Tray



#### Features

- UV resistant plastic
- Water-proof design with IP65
- 16 drop cable ports
- Efficient cable management

#### Specifications

General	
Functionality	Patching   Splicing   Splitting
Enclosure Color	Black
Cable Sealing	Mechanical seal
Inline Cable Ports	1 in 1 out, $\Phi 8$ to $\Phi 16$ mm
Branch Cable Ports	2, $\Phi 8$ to $\Phi 12$ mm
Drop Cable Ports	16, 2.0*3.0mm   3mm
Interface (optional)	N/A, SC/APC, SC/UPC
Adaptors, quantity (optional)	N/A, 16 pre-installed max.
Distribution Type (optional)	N/A, 1 x 8 splitter, 1 x 16 splitter
Split Ratio	Symmetrical
Splice Tray, quantity	1 pre-installed
Splice Tray Capacity, maximum	16   double layer
Front Cover Type	Hinged with lock
Dimension	285*175*98mm
Weight	1.2KG
Mounting	Pole   Wall
Material	
Enclosure	PC+ABS
Splice Tray	ABS
Sealing	Silicone
Optical	

Proprietary information of SIGHTES TECHNOLOGY that may not be reproduced, disclosed or used for any purpose except under the authorized written consent of SIGHTES TECHNOLOGY and may be recalled at any time. Copyright 2022 SIGHTES TECHNOLOGY. All Rights Reserved May 8 2025

**FX-DB416A Series**

Operating Wavelength	1260-1360 & 1460-1650nm
Fiber Mode	Single mode
Fiber Type	G657.A1
Insertion Loss, Adaptor, maximum	0.30dB
Insertion Loss, Splitter, maximum	10.5dB
Return Loss, minimum	55dB
Insertion & Extraction Endurance, minimum	500 durations
<b>Environmental</b>	
Protection Grade	IEC 60529, IP65
Impact Grade	IEC 62262, IK01 Min.
UV protection	UV stabilize
Operation Temperature	-40 to +65°C
Relative Humidity	85% (+30°C) Max.
Atmospheric Pressure	70 to 106 KPa