

Wall-Mounted Mini NAP



Features

- Integrated with splice tray and cable management system
- High strength engineering plastic, compact size, light weight
- 1x8 mini splitter is installed

Specifications

General	
Functionality	Patching Splicing Splitting
Enclosure Color	White
Cable Sealing	Mechanical seal
Branch Cable Ports	4, $\Phi 10$ mm Max.
Drop Cable Ports	8, 2.0*3.0 mm
Interface (optional)	N/A, SC/APC, SC/UPC
Adaptors, quantity (optional)	N/A, 8 pre-installed max.
Distribution Type (optional)	N/A, 1 x 8 splitter
Split Ratio	Symmetrical
Splice Tray, quantity	1, 1 Max.
Splice Tray Capacity, maximum	6 Double layer
Front Cover Type	Screw-fastened
Dimension	133*192*47 mm
Mounting	Wall
Material	
Enclosure	PC+ABS
Splice Tray	ABS
Sealing	Silicon
Optical	
Fiber Mode	Single mode

FX-DB48A Series

Fiber Type	G657, A1
Insertion Loss, Adaptor, maximum	0.3dB
Insertion Loss, Splitter, maximum	10.5dB
Return Loss, minimum	55dB
Insertion & Extraction Endurance	1,000 durations

Environmental

Protection Grade	IEC 60529, IP30
UV protection	UV stabilize
Operation Temperature	-30 to +60°C
Relative Humidity	93% (+70°C) Max.
Atmospheric Pressure	70 to 106 KPa