

Aerial-Mounted NAP Box, One Pre-installed 24-splice Tray



Features

- UV resistant plastic
- Water-proof design with IP65
- 16 drop cable ports
- Efficient cable management

Specifications

General	
Functionality	Patching Splicing Splitting
Enclosure Color	Black
Cable Sealing	Mechanical seal
Branch Cable Ports	4, $\Phi 10$ mm 4, $\Phi 14$ mm
Drop Cable Ports	16, 2.0*3.0mm 3mm
Interface (optional)	N/A, SC/APC, SC/UPC
Adaptors, quantity (optional)	N/A, 16 pre-installed max.
Distribution Type (optional)	1 x 8 splitter, 1 x 16 splitter (optional)
Split Ratio	Symmetrical
Splice Tray, quantity	1, 2 Max.
Splice Tray Capacity, maximum	24 Double layer
Front Cover Type	Hinged with latch
Dimension	196*291*115 mm
Mounting	Aerial
Material	
Enclosure	ABS+PC
Splice Tray	ABS
Sealing	Silicon
Optical	

Proprietary information of SIGHTES TECHNOLOGY that may not be reproduced, disclosed or used for any purpose except under the authorized written consent of SIGHTES TECHNOLOGY and may be recalled at any time. Copyright 2022 SIGHTES TECHNOLOGY. All Rights Reserved May 8 2025

FX-DB816A Series

Fiber Mode	Single mode
Fiber Type (optional)	N/A, G657 A1, G657 A2
Insertion Loss, Adaptor, maximum	0.3dB
Insertion Loss, Splitter, maximum	10.5dB
Return Loss, minimum	55dB
Insertion & Extraction Endurance	1,000 durations
Environmental	
Protection Grade	IEC 60529, IP65
Impact Grade	IEC 62262, IK10
UV protection	UV stabilize
Flammability Rating	UL94-HB
Operation Temperature	-30 to +60°C
Relative Humidity	93% (+70°C) Max.
Atmospheric Pressure	70 to 106 KPa