

### Dome Splice Closure, Heat Shrink Cable Seal, 1 Oval Port & 3 Round Ports



#### Features

- Single-ended, O-ring sealed dome closure for splicing feeder and distribution cables
- Adopt engineering plastic with high-strength to make the closure has longer service life-span
- Splice trays hinged for access to any splice without disturbing other trays

#### Specifications

General	
Enclosure Color	Black
Cable Sealing	Heat shrink
Inline Cable Ports	1 oval port, $\Phi 8$ to $\Phi 25$ mm
Branch Cable Ports	3, $\Phi 8$ to $\Phi 16$ mm
Splice Tray, quantity (optional)	N/A, 4 pre-installed max.
Splice Tray Capacity, maximum	12   Double Layer
Splicing Capacity, Single Fusing, maximum	48
Closure Sealing Type	Dome-to-base clamp with O-ring
Dimension	310*190*190mm
Flash Test Valve (optional)	N/A, Pre-installed
Mounting (optional)	Pole, Aerial
Material	
Enclosure	PP
Splice Tray	ABS
Sealing	Rubber
Environmental	
Protection Grade	IEC 60529, IP68
Impact Grade	IEC 62262, IK08
UV protection	UV stabilize
Flammability Rating (optional)	N/A, UL94-HB
Operation Temperature	-40 to +60°C
Atmospheric Pressure	70 to 106 KPa