

Aerial-Mounted Dome Splice Closure, Heat Shrink Cable Seal, 1 Oval Port & 6 Round Ports



Features

- Single-ended, O-ring sealed dome closure for splicing feeder and distribution cables
- Adopt engineering plastic with high-strength to make the closure has longer service life-span
- Splice trays hinged for access to any splice without disturbing other trays

Specifications

General	
Enclosure Color	Black
Cable Sealing	Heat shrink
Inline Cable Ports	1 oval port, $\Phi 8$ to $\Phi 31$ mm
Branch Cable Ports	6, $\Phi 6$ to $\Phi 22$ mm
Splice Tray, quantity (optional)	N/A, 6 pre-installed Max.
Splice Tray Capacity, maximum	24 Double layer
Splicing Capacity, Single Fusing, maximum	144
Closure Sealing Type	Dome-to-base clamp with O-ring
Dimension	500*200*200mm
Flash Test Valve (optional)	N/A, Pre-installed
Mounting	Aerial
Material	
Enclosure	PP
Splice Tray	ABS
Sealing	Rubber
Environmental	
Protection Grade	IEC 60529, IP68
UV protection	UV stabilize
Flammability Rating (optional)	N/A, UL94-HB
Operation Temperature	-40 to +65°C
Atmospheric Pressure	70 to 106 KPa