


Horizontal Splice Closure, Mechanical Cable Seal



Features

- UV resistant plastic
- Hinged buckle design
- Spacious enough for fiber winding and storing
- Efficient cable management

Specifications

General	
Enclosure Color	Black
Cable Sealing	Mechanical
Cable Capacity	4 Round 10.0-18.0 mm
Splice Tray, quantity (optional)	N/A, 3 pre-installed max.
Splice Tray Capacity, maximum	24 Double Layer
Splicing Capacity, Single Fusing, maximum	72
Closure Sealing Type	Base-to-base latch with O-ring
Dimension	490*200*120 mm
Mounting (optional)	Aerial, Buried
Material	
Enclosure	PP
Splice Tray	ABS
Sealing	Rubber
Environmental	
Protection Grade	IEC 60529, IP68
Impact Grade	IEC 62262, IK08
UV protection	UV stabilize
Operation Temperature	-40 to +65°C
Atmospheric Pressure	70 to 106 KPa

Proprietary information of SIGHTES TECHNOLOGY that may not be reproduced, disclosed or used for any purpose except under the authorized written consent of SIGHTES TECHNOLOGY and may be recalled at any time. Copyright 2022 SIGHTES TECHNOLOGY. All Rights Reserved May 8 2025